



55 Bristol Dr.
S. Easton MA 02375
P: 1 (800) 225-0430
F: 1 (508) 238-0103
Web: www.SolarSeal.com
Email: Sales@SolarSeal.com

Warranty on ClearShield Glass

1) Performance

- a) ClearShield Glass resists staining and is easier to clean than ordinary glass. In most cases, it requires cleaning less than half as often.
- b) The service life of ClearShield Glass depends mainly on:
 - i) atmospheric abrasion from wind and sand;
 - ii) the use of abrasive or alkaline cleaning products;
 - iii) alkalinity from hard water deposits and runoff from building materials such as concrete and brickwork.

The greatest enemies of glass are moisture and alkalinity. Normal glass can be attacked and stained very easily. ClearShield Glass resists such attack but can be affected by prolonged exposure.

- c) To extend the life of ClearShield Glass, Solar Seal has a special line of after-care products available which contain no abrasives, do not leave a film or residue and neutralize alkalinity.
- d) As a guide, the service life of ClearShield Glass installed externally and vertically is up to ten (10) years for residential and commercial architectural glass situations in typical urban or suburban locations and under normal environmental conditions when the recommended after-care program is followed. The service life may be less in seaside or industrial areas and greater in country locations.
- e) ClearShield Glass performs indefinitely if a simple “booster” application is made whenever the service life nears its end, i.e. the performance of ClearShield Glass becomes noticeably reduced in terms of ease of cleaning and resistance to staining.

2) Warranty

a) Solar Seal administers a quality control program including routine quality checks to ensure that:

i) ClearShield bonds chemically and becomes an integral part of the glass surface:

ii) a uniform coverage is achieved across the glass surface.

b) Solar Seal will warranty its ClearShield Glass products to its customer for the following terms:

Furniture Glass	For up to 10 years
Sandblasted Glass	For up to 10 years
Textured Glass	For up to 10 years
Insulated Glass Units	For up to 10 years
Shower Enclosures	For up to 8 years

c) This warranty is based upon

i) glass being installed in a vertical position (at an angle greater than forty five degrees (45°)) with the exception of furniture glass.

ii) glass being installed at a distance greater than two-thousand feet (2000') from a large body of water.

iii) Solar Seal's after-care product guidelines are followed.

d) This warranty is valid for only one-half (1/2) the specified time frame if the after-care program is not followed.

e) Should the glass not perform within Solar Seal's standard quality tests as determined by Solar Seal and all the above guidelines have been followed, Solar Seal will at its discretion:

i) reapply the product at no-charge to its customer or

ii) resupply the ClearShield Glass at no-charge to its customer.